



Description:

STARDEK Grout Mix is an acrylic modified cementitious material. When combined with **STARDEK RESIN** it produces an excellent multi-purpose decorative floor coating system. **STARDEK** is specifically made for either interior or exterior applications. Use prior to coating with **STARDEK** coating materials.

Benefits:

- Easy to mix
- Fast Hardening
- Excellent bond to most substrates
- VOC Compliant
- Little or no shrinkage cracks
- Decorative long lasting finish
- Hard durable surface

Packaging:

STARDEK Grout Mix available in 36 pound bags. **STARDEK Resin** is available in 5 gallon pails. **STARDEK** should always be used in combination with **STARDEK Resin**. Also available in kits consisting of 5 bags of **STARDEK Grout Mix** and 5 gallons of **STARDEK Resin**.

Approximate Coverage:

One **STARDEK** kit (see packaging section above) will cover approximately 875 sqft.

Limitations:

- Do not apply at temperatures below 50° F. Cold temperatures will interfere with the curing process.
- **STARDEK** is designed to be sprayed or trowelled and after application should be kept from rain or any other source of moisture for a few hours in order to dry.

Test Results:

STARDEK Material

Shear Bond Strength	250 PSI
Tensil Strength	925 PSI
Compressive Strength	4365 PSI
Flexural Strength	1830 PSI
Impact Strength	37 in. lbs.
Abrasion Resistance	0.3%

Storage and Handling:

Store **STARDEK Cements** in a cool, dry area and protect **STARDEK Resin** from freezing. Keep all bags of **STARDEK** free from any dampness or moisture. Partial pails of **STARDEK Resin** can be resealed for future use. There will be no change in physical properties and effectiveness will not be impaired. Dispose of empty containers properly according to current local, State, and Federal regulations.

Shelf Life:

Average shelf life is twelve months from shipping date if stored in a cool dry area. To guarantee shelf life, keep away from dampness or moisture.

Cleanup:

Before **STARDEK Cements** harden, clean all mixing and application tools with water.

Health and Hazard Information:

Use product with adequate ventilation and personal protection.

Availability:

Product is available from Color-Crown Corporation or any of it's authorized distributors.

STARDEK® mfg. by:
Color-Crown Corporation
928 Sligh Ave Seffner, FL 33584
(800) 282-1599 ♦ FAX (813) 655-8830

The Choice of
Professionals. . . .