



ColorCrown Corporation  
 928 Sligh Ave – Seffner FL 33584  
 (800) 282-1599

---

## PAVER SAVER

### TECHNICAL BULLETIN

**Description:**

Paver Saver, a 25% solids solution sealer, is a solventborne; single component acrylic blend. It is specially formulated to provide an excellent balance of UV stability with superior mar and abrasion resistance. This product penetrates deeply into all concrete or paver surfaces providing long term durability while protecting against oils, dirt, traffic and mildew growth.

**Typical Properties:**

- °Chemical Name.....Acrylic
- °Color.....Clear
- °Weight/Gallon.....7.69
- °UV Resistance.....Excellent
- °Diluent.....Aromatic
- °VOC.....Less than 700 gm/l

**Directions For Use:**

Proper surface cleaning and preparation should always be carried out prior to applying Paver Saver. Note: if mildew is present, bleach pavers first. Make sure you properly rinse before applying acid to surface. The area to be cleaned must be properly acid washed before sealing. Mix 1 pint muriatic acid per gallon of water. Spread acid over Pavers and

pressurewash, rinse thoroughly. **Surface must be totally dry before applying.** If other stains are present such as oil or rust, use a degreaser, or a rust remover prior to acid etching.

**Application:**

Paver Saver can be applied by sprayer, roller, or brush. Material can be stored 12 months at room temperature and in original sealed container.

**NOTE: Paver Saver is not recommended as a replacement for STARDEK II Sealer.**

**Coverage:**

The coverage rate of Paver Saver can be anywhere in from 150 to 300 square feet depending on the porosity of the surface. Dilution is not recommended.

**Packaging:**

Available in 1 gallon or 5 gallon pails.

*The Choice Of Professionals*

The information contained herein is based on data obtained by our own research and other recognized manufacturers and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. This information is furnished upon the condition that the person receiving it shall make his own tests to determine the suitability thereof for his particular purpose.

REV 08/23/07